

Reciprocating pillow packing machine



Features:

1. Double transducer control, flexible bag length ,operator needn't to adjust the unloading working, saving time and saving films.
2. Touchable human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity electric color mark tracking AND digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Reciprocating type sealing device, firmer sealing, no wasting in mould sealing cutter.
7. Terminal sealing device, more beautiful bag shape, improving products level.
8. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
9. Simple driving system, reliable working, convenient maintenance.
10. All the controls are achieved by software, convenient for function adjusting and upgrading.

Application

Suitable for packing regular objects such as biscuit, bread, instant noodle, moon cakes, industrial parts, paper box or trays.

Specification

Model	KL-350W	KL-450W	KL-600W
Film width	Max.350mm	Max.450mm	Max.600mm
Bag length	110-330mm	120~450mm	120~450mm
Bag width	30-130mm	50~160mm	50~200mm
Product height	10-80mm	10~120mm	10~150mm
Film roll diamete	Max.320mm		
Packing speed	30-120bag/min	20~75bag/min	
Power supply	220V 50/60Hz 2.4KW	220V,50/60HZ,3.2KVA	220V,50/60HZ,3.6KVA

Size(mm)	(L)3670*(W)820*(H)1410	(L)3980×(W)860×(H)1530	(L)3980×(W)970 ×(H)1530
Weight	650kg	960kg	1160kg