

# DONE-E

## QMO-系列无氧化烘箱 Inert Gas Oven

100ppm |



# 【无氧化烘箱】 INERT GAS OVEN

## QMO-2、QMO-3、QMO-5

### 主要规格和技术参数 Specifications

型号 Model		QMO-2	QMO-3	QMO-5
含氧量Oxygen content		100ppm		
电源 Power supply		AC380V 3 4W 50HZ		
功率(KVA) Power (KVA)		13	10.5	12
工作环境温度 Operating temperature		5 ~ +35		
性能 Performance	温度范围 Temperature range	+60 ~ +500	+60 ~ +300	
	温度波动度 Temperature fluctuation	± 0.5		
	温度均匀性 Temperature uniformity	300 ± 4.5    500 ± 10	200 ± 3    300 ± 4	
	升温时间 Temperature heat-up rate	70分钟以内 (室温 ~ +500 ) Within 70 min(Ambient temperature ~ +500 )	40分钟以内 (室温 ~ +250 ) Within 40 min(Ambient temperature ~ +250 )	
结构 Construction	外壳 Exterior Material	防锈处理冷轧钢板(表面喷塑处理)Cold-nolled rust-proof steel plate(Urethane resin electrostatic coating)		
	内胆 Interior material	SUS304 # 日制阳极不锈钢 SUS304 # Stainless steel		
	隔热材料 Insulation	玻璃棉 Glass wool		
	加热器 Heater	覆套式电热器 Sheathed Heater		
	进气口 Inlet	( N2 or Clean air) 6mm		
	出气口 Outlet	5mm自动开启排风门 5mm Automatic exhaust door		
温度控制系统 Temperature controller	调节方式 Control mode	PID控制方式 PID control		
	运转方式 Operating mode	定值运转, 程序运转 Constant operation , Programme operation		
	设定范围 Setting range	0 ~ +500	0 ~ +300	
	设定方式 Setting mode	数字式 Digital		
	显示方式 Display	LED数字显示 LED display		
	传感元件 Sensor	K型热电偶 Thermocouple type K		
	安全保护 Safety system	输入断线检测功能、上限温度过热报警功能、蜂鸣器报警功能、自动温度过热防止功能、自行诊断功能 Input burn-out delection function、Upper temperature limit alarm、Buzzer alarm、Over-heat protection、Self diagnostic function		
定时功能 Timer	0.1 ~ 999.9H			
安全保护装置 Safety devices	电源用漏电断路器、电机温度保护开关、温度保险丝、独立温度过升防止装置 Leakage breaker for power supply、Air circulator temperature switch、Thermal fuse、Overload and short circuit protection for heater、Over-heat protect			
搁板承重能力(kg) Shelf weight capacity	20			
内容积(L) Inside capacity(L)	150	394	243 x 2	
重量约(kg) Weight(kg)	230	350	440	
内部尺寸(W x H x D)mm Inside dimensions	500 x 600 x 500	710 x 910 x 610	710 x 560 x 610(双箱 Dual Oven)	
外部尺寸(W x H x D)mm Outside dimensions	1180 x 1045 x 800	1380 x 1390 x 960	1460 x 1790 x 960	
附件 Accessories	搁板 Shelf	2块 Blocks		
	使用说明书 Instruction manual	1册 Set		
选购品 Option	可编程温控器、记录器、六点温度显示器、三色指示灯 Programmable Temperatruce Controller、Recorder、Light Tower			

\*1:在环境温度25 时,空载条件下测得的数据;

\*2:外尺寸包括鼓风机罩壳和脚轮高度。

\*1:The test condition is at 25 ambient temperature non-loaded.

\*2:The outside dimensions including motor cover and wheel.

本资料的技术信息如有改动,恕不另行通知;产品以实物为准,图片仅供参考。

Specifications are subject to change without notice due to design improvements.The picture in the specimen are consult only ,If there is fluctuation,according to the real object please.



上海旦顺实业有限公司  
SHANG HAI DONE-E INDUSTRY CO.,LTD.

上海市沪亭路71弄35号  
No. 71 Huting Road Shanghai, China  
ZIP Code:201615  
Tel: +86-021-3769 3997  
Fax: +86-021-3783 2075  
Email: sale@done-e.com  
Web: www.done-e.com